



FLIR T600 bx

The best ergonomics and an economical new thermal resolution for intensive inspections

Inspect high and low comfortably all day and capture stunning shots effortlessly with the latest addition to thermal imaging's most flexible line of handheld cameras.

A new high IR resolution – Crisp thermal images with 172,800 pixels (480 x 360) for the better detection, picture quality, and temperature measurements from long range.

Exclusive rotating optical block – Work smarter. Scan targets overhead, and from other tough angles effortlessly with the lens system that lets you point 120° up or down while keeping the display in easy view.

MSX® enhancement – Multi-Spectral Dynamic Imaging adds visible spectrum definition to IR images in real time for excellent thermal detail to help you instantly recognize the problem locations.

Remote control and streaming video via Wi-Fi – Control camera functions, stream video for live monitoring, and import images and data from the camera using the FLIR Tools Mobile app on your smartphone or tablets so you can share critical information quickly from the field.

Auto-Focus precision – FLIR T-Series cameras offer both manual control and the fastest auto-focus in the industry to snap in ultimate clarity and accuracy.

Auto orientation – Automatically orients onscreen temperature measurement data whether in portrait or landscape mode.

Accuracy – Calibrated within +/- 2°C or +/- 2% of reading.


Multiple measurements – Report all the details with 10 measurement spots, 5 box areas, Delta T temperature differential, isotherm, and auto hot/cold markers.

METERLINK® – Wirelessly transmit vital diagnostic data from clamp and moisture meters directly to the camera for annotating thermal images to further support findings.

See specification chart on back for accessories.



Wi-Fi connectivity with FLIR Tools Mobile app



Original IR Image (left); MSX® enhancement (right)




Built-in 5MP digital camera, LED lamps, laser pointer, diopter, rotating lens, image capture button and auto/manual focus.



Auto orientation keeps on-screen data upright

Applications



Missing insulation - Solar cell failure - Moisture intrusion

Radiant heat tubing - Cold draft - Air infiltration

Imaging specifications

FEATURES	FLIR T600 bx
Temperature range	-40°C to 350°C (-40°F to 662°F)
Thermal sensitivity (N.E.T.D)	<0.04°C at 30°C
Digital zoom	4X continuous
Focus	Manual or automatic (one shot)
LCD Image sketch	Draw on stored images using the touchscreen
Multi-Spectral Dynamic Imaging (MSX)	IR image with enhanced detail presentation
Frame rate	30Hz
Field of view/Minimum focus distance/FOV match	25° x 19° / 0.82ft (0.25m) / Field of View Match where Digital Image FOV adapts to the IR lens
Detector type - Focal plane array (FPA) uncooled microbolometer	480 x 360 pixels
Display	Built-in touch-screen 4.3" color LCD (800 x 480 pixels)
Image modes	Thermal/Visual/P-i-P (Resizable and movable)/MSX and Thumbnail Gallery
Automatic image adjustment	Continuous/manual; linear or histogram based; possible to lock max, min or span temperature
Manual image adjustment	Level/span/max/min
Image storage	1000 radiometric JPEG images (SD card memory)
Image annotation	Voice (60 sec); text comments, Sketch
Periodic image storage	7 seconds to 24 hours (IR) and 14 seconds to 24 hours (IR and visual)
Video lamp and laser pointer	Built-in dual LED lamps plus onboard laser pointer
Laser classification/type	Class 2/Semiconductor AlGaInP Diode Laser: 1mW/635nm (red)
Set-up controls	Mode selector, color palettes, configure info to be shown in image, local adaptation of units, language, date and time formats, and image gallery
Measurement modes	10 Spotmeters, 5 Box areas, Isotherm, Auto hot/cold spot, Delta T
Measurement presets	6 presets: center spot; hot spot (box max); cold spot (box min); no measurements; user preset 1; user preset 2
Measurement correction	Reflected ambient temperature & emissivity correction
Humidity alarm	Including dewpoint alarm
Insulation alarm	Alerts to temperature difference indicating voids
Video recording in camera and video streaming	Non-radiometric IR-video recording (MPEG-4 to memory card), Visual and Radiometric IR-video streaming (Full dynamic to PC using USB or Wi-Fi), and Non-radiometric IR-video streaming (MPEG-4 using Wi-Fi and uncompressed colorized video using USB)
Battery type/operating time	Li-Ion/ 2.5 hours, Display shows battery status
Charging system	In camera AC adapter/2 bay charging system
Shock / vibration / encapsulation; safety	25G, IEC 60068-2-29 / 2G, IEC 60068-2-6 / IP54; EN/UL/CSA/PSE 60950-1
Dimensions/weight	5.6 x 7.7 x 3.7" (143x196x94mm)/2.87lbs (1.3kg), including battery
Accessories included	SD Memory Card, 100-260V AC adaptor/charger, two Li-Ion rechargeable batteries, 2-bay battery charger, power supply (with multi-plugs), FLIR Tools™ software, USB cable, video cable, Bluetooth® headset, lens cap, neckstrap, and hard case

Ordering information

55901-4102 FLIR T600bx Thermal imaging IR camera (480x360) with Wi-Fi and standard 25° Lens
 55901-4103 FLIR T600bx Thermal imaging IR camera (480x360) with Wi-Fi plus 45° Lens



* After product registration on www.flir.com

ACCESSORIES

T197914 IR lens, f=41.3 mm (15°) with case
T197922 IR lens, f=24.6 mm (25°) with case
T197915 IR lens, f=13.1 mm (45°) with case
T198059 Close-up IR lens, 2.9x (50 µm) with case
T198060 Close-up IR lens, 5.8x (100 µm) with case
T198166 IR lens, f=88.9 mm (7°) with case and support
T198065 IR lens, f=6.5 mm (80°) with case

T198066 Close-up IR lens, 1.5x (25 µm) with case
T910814 Power supply, incl. multi plugs
T198506 Li-Ion battery pack 3.7V 29Wh
T911230ACC . Memory card SDHC 4 GB
1910423 USB cable Std A <-> Mini-B
T198509 Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
T910930ACC . HDMI type C to DVI cable 1.5 m
T910891ACC . HDMI type C to HDMI type A cable 1.5 m

T198625 Hard transport case
T198495 Pouch
T198497 Large eyecap
T198498 Tripod adapter
T198496 Stylus pen
T198499 Neck strap
T197771ACC . Bluetooth headset
T198583 FLIR Tools+ (license only)
T911093 Tool belt



FLIR Commercial Systems
 Luxemburgstraat 2
 2321 Meer
 Belgium
 Tel. : +32 (0) 3665 5100
 Fax : +32 (0) 3303 5624
 E-mail : flir@flir.com

FLIR Systems AB
 Sweden
 Tel. : +46 (0)8 753 25 00

FLIR Systems UK
 Tel. : +44 (0)1732 220 011

FLIR Systems GmbH
 Germany
 Tel. : +49 (0)69 95 00 900

FLIR Systems France
 Tel. : +33 (0)1 60 37 55 02

FLIR Systems Italy
 Tel. : +39 (0)2 99 45 10 01

FLIR Commercial Systems
 Spain
 Tel. : +34 91 573 48 27

FLIR Systems, Middle East FZE
 Dubai - United Arab Emirates
 Tel. : +971 4 299 6898

FLIR Systems Russia
 Tel. : +7 495 669 70 72

www.flir.com
 NASDAQ: FLIR