

**SAFETY IS OUR PRIORITY****MS2002+ / ACCELERATION SENSOR****SENSOR**

MS2002+ to be linked to motion recorders such as :

- MR2002-SM16-K
- MR2002-SM24-K

**DATASHEET : MS2002+**

The micromachined capacitive accelerometer has become an attractive alternative against traditionally used FBAs.

It's small dimensions, rugged construction and excellent reliability makes it especially suitable for unattended free-field instruments and instrumentation of structures, such as nuclear power plants, dams and seismic alerting systems.

## MS2002+ / ACCELERATION SENSOR

The well proven technology of silicon micromachined capacitive sensors has been further improved by optimizing the sensor structure. Integration of electronics into an application specific IC results in a small high precision accelerometer which shows environmental and reliability performance similar to integrated circuits. This accelerometer, built as triaxial device, suits ideally into seismic instrumentation.

The DC coupled output in combination with the very low short and long-term drift provides true engineering data that require no post-processing. The micromachined capacitive accelerometer has become an attractive alternative against traditionally used Force Balanced Accelerometers. Its small dimensions, rugged construction and excellent reliability makes it especially suitable for unattended free-field instruments and instrumentation of structures, such as nuclear power plants, dams and seismic alerting systems. The sensors are factory calibrated and require no re-calibration. They are equipped with a fully comprehensive self-test function.

### Technical Specification

#### Principle

The acceleration sensing element is based on a micromechanical silicon chip, an ASIC for signal conditioning, and an EEPROM for storage of the calibration data. The micromechanical capacitive chip is manufactured using a 3-wafer silicon bulk-micromachining fusion bonding process. The signal conditioning IC translates the capacitance variation of the sensor chip into a calibrated output voltage. The gain, offset and nonlinearity corrections are programmed digitally during manufacturing.

Hysteresis	None
Noise	Typ. 18 $\mu\text{V}/\sqrt{\text{Hz}}$
Shock survival	6000 g (0.5 ms half sine)
Vibration survival	20 g RMS (random noise 20-500 Hz, 30 minutes)
Operating temperature	- 30 to 70°C
Offset (at 0g)	2.5 V $\pm$ 200 $\mu\text{V}/^\circ\text{C}$
Cross axis sensitivity	0.030 V/g
Orientation	Triaxial, horizontal (floor) mounting or vertical (wall) mounting
Non-Linearity	< 0.8 % of full scale
Frequency response Linear	0 to 150 Hz (accuracy $\pm$ 1%)
Dynamic range (RMS)	> 84 dB (DC to 50 Hz)

#### MS2002+ triaxial Sensor (unipolar)

Measuring range	$\pm$ 1 g
Sensitivity	2 V/g $\pm$ 400 ppm/ $^\circ\text{C}$
Supply voltage	+ 12 V (+10 % / -30 %)
Current consumption	Typ. 6 mA @ 12 V
Output voltage	2.5 V $\pm$ 2 V

#### MS2002+ triaxial Sensor (bipolar)

Measuring range	$\pm$ 1 g	$\pm$ 2 g	$\pm$ 10 g
Sensitivity	2 V/g	1 V/g	0.2 V/g $\pm$ 400 ppm/ $^\circ\text{C}$
Supply voltage	$\pm$ 5 V ( $\pm$ 5%)		
Current consumption	Typ. 6 mA @ 5V		4 mA @ -5 V
Output voltage	0 V $\pm$ 2 V		

#### Physical Characteristics

Housing	Aluminum, 80 x 75 x 57 mm (W x L x H)
Connector	Metallic self-latching push-pull connector with LEMO
Weight	0.5 kg
Protection degree	IP 65 (splash-proof)
Optional	Mounted inside MR2002 recorder

#### Ordering Information

MS2002+ triaxial, horizontal mounting	1 g FS	14112001
MS2002+ triaxial, horizontal mounting	2 g FS	14112002
MS2002+ triaxial, horizontal mounting	10 g FS	14112003
MS2002+ triaxial, vertical mounting	x = g FS, see above	1411201x
MS2002+ uniaxial, horizontal mounting, vertical axis	x = g FS, see above	1411221x
MS2002+ uniaxial, horizontal mounting, horizontal axis	x = g FS, see above	1411220x



MS2002+ with LEMO connector



Edificio Antalia  
Albasanz, 16  
28037 MADRID  
Tel. 91 567 97 00  
Fax: 91 570 26 61

[www.alavaingenieros.com](http://www.alavaingenieros.com)

Torre Mapfre-Vila Olímpica  
Marina, 16 - Planta 11-C2  
08005 BARCELONA  
Tel. 93 459 42 50  
Fax: 93 459 42 62

[alava@alava-ing.es](mailto:alava@alava-ing.es)

[www.syscom.ch](http://www.syscom.ch)  
 [info@syscom.ch](mailto:info@syscom.ch)