

Owl 640 Mini VIS-SWIR

VGA resolution, low power, VIS-SWIR camera

640 x 512 • 15 μm x 15 μm pixel pitch • VIS-SWIR Technology •



Key Features and Benefits

TEC-less Visible SWIR technology

- **TEC-less Visible SWIR**

Enables ultra low power

- **15 μm x 15 μm pixel pitch**

Enables highest resolution VIS-SWIR image

- **Ultra high intrascene dynamic range**

Enables simultaneous capture of bright & dark portions of a scene

- **Ultra compact, Rugged, No fan**

Specially designed for integration into small OEM platforms

Resolution	640 x 512
Ultra Low Power	<2.5W
Optical Interface	C-mount
Wavelength Range	VIS-SWIR

Specification for OWL SWIR 640 Mini

Sensor Type	InGaAs PIN-Photodiode
Active Pixel	640 x 512
Pixel Pitch	15µm x 15µm
Active Area	9.6mm x 7.68mm
Spectral response ¹	0.4µm to 1.7µm
Noise (RMS)	<195 electrons Low Gain (176 electrons typical)
Quantum Efficiency	Peak >85% (>73% @ 1.064µm, 78% @ 1.55µm)
Pixel Well Depth	Low Gain: 600Ke-
Pixel Operability	>99.5%
Output Format	14 bit CameraLink (base configuration)
Exposure time	1µs to 1 / frame rate
Shutter mode	Global shutter
Frame Rate	Up to 120Hz programmable
Optical Interface	C mount
Camera Setup / Control	Cameralink
Trigger interface	Trigger IN and OUT - TTL compatible
Power supply	12V DC ±10%
TE Cooling	None
Functions controlled by serial communication	Exposure, intelligent AGC
Camera Power Consumption ²	< 2.5W
Operating Case Temperature ³	-20°C to +55°C
Storage Temperature	-30°C to +60°C
Dimensions & Weight	42mm x 42mm x 67mm / 282g

Raptor Photonics Limited reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.

Ordering Information

Camera

OWL 640 SWIR Digital LP C-Mount	OWL1.7-VS-CL-LP-640
OWL Power Supply Cable	RPL-HR4-K

Optional Accessories

EPIX(R) base notebook CL card	RPL-EPIX-ECB1-34
EPIX(R) base notebook CL card	RPL-EPIX-ECB1-54
Optical SWIR lenses ⁴	RPL-xx-xxxx

Note 1: Optional filters available: Low, High or bandpass

Note 2: Measured @ 30°C

Note 3: Extended Operating Temperature range on request

Note 4: Please consult us to check our range of lenses




Edificio Antalia, Albasanz 16. 28037 Madrid
+34 91 567 97 00 | alavaingenieros.com | alava@grupoalava.com
Madrid | Barcelona | Zaragoza | Lisboa | Lima | Quito | Texas

Demo is available on request.
Pricing AOR subject to volumes.

Detailed technical drawings
can be downloaded at
www.raptorphotonics.com

Quantum Efficiency



Applications

- 860, 1064 & 1550nm laser line detection
- Hand Held Goggles
- Vision enhancement
- Machine vision
- Beam profiling

Document #: INOWL1.7-VS-CL-LP-640 / AE 0116R1



Willowbank Business Park
Larne, Co Antrim
BT40 2SF,
Northern Ireland

T: +44(0)2828 270 141
E: sales@raptorphotonics.com
www.raptorphotonics.com

