

POS MV™ WAVEMASTER SPECIFICATIONS

MAXIMIZE YOUR ROI WITH POS MV WAVEMASTER

POS MV Wavemaster is a user-friendly, turnkey system designed and built to provide accurate attitude, heading, heave, position, and velocity data of your marine vessel and onboard sensors. POS MV is proven in all conditions, and is the georeferencing and motion compensation solution of choice for the hydrographic professional.

POS MV blends GNSS data with angular rate and acceleration data from an IMU and heading from GPS Azimuth Measurement System (GAMS) to produce a robust and accurate full six degrees-of-freedom position and orientation solution.



PERFORMANCE SUMMARY - POS MV WAVEMASTER ACCURACY

POS MV 320	DGPS	RTK	Accuracy During GNSS Outage
Position	0.5 - 2 m ¹	Horizontal: +/- (8 mm + 1 ppm x baseline length) ² Vertical: +/- (15 mm + 1 ppm x baseline length) ²	~ 9 m for 60 s total outages (RTK) ~ 3 m for 30 s total outages (RTK) ~ 2 m for 60 s total outages (IAPPK)
Roll & Pitch	0.03°	0.02° (0.015° with post processing)	0.04°
True Heading	0.015° with 4 m baseline 0.03° with 2 m baseline 0.06° with 1 m baseline	-	<2° per hour degradation (negligible for outages <60 s)
Heave TrueHeave™	5 cm or 5% ³ 2 cm or 2% ⁴	5 cm or 5% ³ 2 cm or 2% ⁴	5 cm or 5% ³ 2 cm or 2% ⁴

PCS OPTIONS

COMPONENT	DIMENSIONS	WEIGHT	TEMPERATURE	HUMIDITY	POWER
Rack Mount PCS	L = 483mm, W = 334mm, H = 444mm	3.9 Kg	-20 °C to +70°C	10 - 80% RH ³	110/230 Vac, 50/60 Hz, auto-switching 40 W
Small Form Factor PCS	L = 167mm, W = 185mm, H = 68mm	2.5 Kg	-20 °C to +60 °C	0- 100% RH	24 Vdc, 35 W (peak)

HOUSING AND ADAPTOR PLATES

COMPONENT	DIMENSIONS	IP RATING
Waterproof Housing	L = 209mm, H = 196mm	IP68
Adaptor Plate	L = 135mm, W = 142mm, H = 19mm	IP68

INERTIAL MEASUREMENT UNIT (IMU)

TYPE	DIMENSIONS	WEIGHT	TEMPERATURE
IMU-37	L = 158 mm, W = 158mm, H = 124 mm	2.5 Kg	-40 °C to +60 °C
IMU-42	L = 158 mm, W = 158 mm, H = 124 mm	2.5 Kg	-40 °C to +60 °C

GLOBAL NAVIGATION SATELLITE SYSTEM (GNSS)

COMPONENT	DIMENSIONS	WEIGHT	TEMPERATURE	HUMIDITY
GPS Antenna	(Diameter) 165mm, W = 76mm	0.64 Kg	-40 °C to +70 °C	0-100% RH

¹ Depending on quality of differential corrections

² Assumes 1 m IMU-GNSS antenna offset

³ Whichever is greater, for periods of 20 seconds or less

1. ETHERNET INPUT OUTPUT

Ethernet Parameters	(10/100/1000 base-T) Time tag, status, position, attitude, heave, velocity, track and speed, dynamics, performance metrics, raw IMU data, raw GPS data
Display Port	Low rate (1 Hz) UDP protocol output
Control Port	TCP/IP input for system commands
Primary Port	Real-time (up to 200 Hz) UDP protocol output
Secondary Port	Buffered TCP/IP protocol output for data logging to external device

2. SERIAL RS232 INPUT OUTPUT

4 COM Ports	User assignable to: NMEA output (0-4), Binary output (0-4), Auxiliary GPS input (0-2), Base GPS correction input (0-2)
-------------	--

3. NMEA ASCII OUTPUT

Parameters	NMEA Standard ASCII messages: Position (\$INGGA), Heading (\$INHDT), Track and Speed (\$INVTG), Statistics (\$INGST), Attitude (\$PASHR, \$PRDID), Time and Date (\$INZDA, \$UTC).
Rate	Up to 50 Hz (user selectable)
Configuration	Output selections and rate individually configurable on each assigned com port.

4. HIGH RATE ATTITUDE OUTPUT

Parameters	User selectable binary messages: attitude, heading, speed
Rate	Up to 200 Hz (user selectable)
Configuration	Output selections and rate individually configurable on each assigned com port.

5. AUXILIARY GPS INPUTS

Parameter	NMEA Standard ASCII messages: \$GPGGA, \$GPGST, \$GPGSA, \$GPGSV. Uses Aux input with best quality.
Rate	1 Hz

6. BASE GPS CORRECTION INPUTS

Parameter	RTCM V2.x, RTCM V3.x, CMR and CMR+, CMRx input formats accepted. Combined with raw GPS observables in navigation solution.
Rate	1 Hz

6. DIGITAL I/O

1PPS	1 pulse-per-second Time Sync output, normally high, active low pulse
Event Input (2)	Time mark of external events. TTL pulses > 1 msec width, rising or falling edge, max rate 200 Hz.

7. USER SUPPLIED EQUIPMENT

- PC for POS Controller (Required for configuration): Pentium 90 processor (minimum), 16 MB RAM, 1 MB free disk space, Ethernet adapter (RJ45 100 base T), Windows 98/2000/NT/XP/Windows 7
- PC for POSpac Post-processing Software: Pentium III 800Mhz or equivalent (minimum), 512 MB RAM, 400 MB free disk space, USB Port (For Security Key), Windows XP or Windows 7.

Scan the QR Code on your mobile device to access information on POS MV



Headquarters: 85 Leek Crescent Richmond Hill, ON Canada L4B 3B3 T 905.709.4600 F 905.709.6027
United Kingdom: Forester's House, Old Racecourse Oswestry UK SY10 7PW T 44 1691 659359 F 44 1691 659299
Texas: 17461 Village Green Drive, Houston TX USA 77040 T 713.896.9900 F 713.896.9919
www.applanix.com

2013, Applanix, A Trimble Company. All rights reserved. Applanix and the Applanix logo are trademarks of Applanix Corporation registered in the Canadian Patent and Trademark Office and other countries. POS LV and POSpac are registered trademarks of Applanix Corporation. All other trademarks are the property of their respective owners. Information subject to change without notice. April, 2013



capture everything. precisely.